



(11) 2701-0770

(11) 9.7074-5477

rcm@rcmferramentas.com.br

www.rcmferramentas.com.br

RECOMENDAÇÃO PARA CORTAR MATERIAL SÓLIDO

Passo de dente variável	
Corte transversal mm	dentes por polegada dpp
de 550	0,75/1,25
380 - 750	1/1,3
250 - 550	1,4/2
120 - 350	2/3
80 - 140	3/4
60 - 110	4/6
40 - 70	5/7 5/8
30 - 60	6/10
20 - 40	8/11 8/12
até 25	10/14

RECOMENDAÇÃO PARA CORTAR TUBOS E ESTRUTURAS

Estruturas de parede fina (ângulo de Rake 0° - 7°)

ESPESSURA DA PAREDE MM	20	40	60	80	100	120	150
2	14	14	14	14	14	14	10/14
3	14	14	14	14	10/14	10/14	8/11 8/12
4	14	14	10/14	10/14	8/11 8/12	8/11 8/12	6/10
5	14	10/14	10/14	8/11 8/12	8/11 8/12	6/10	6/10
6	14	10/14	8/11 8/12	8/11 8/12	6/10	6/10	5/7 5/8
8	14	8/11 8/12	6/10	6/10	5/7 5/8	5/7 5/8	5/7 5/8
10	-	6/10	6/10	5/7 5/8	5/7 5/8	5/7 5/8	-

Estruturas de parede pesada (ângulo de rake positivo)

ESPESSURA DA PAREDE MM	80	100	120	150	200	300	500	750
10	-	-	-	4/6	4/6	4/6	3/4	2/3
15	4/6	4/6	4/6	4/6	4/6	3/4	2/3	2/3
20	4/6	4/6	4/6	4/6	3/4	3/4	2/3	2/3
30	4/6	4/6	4/6	3/4	3/4	2/3	2/3	2/3
50	-	-	3/4	3/4	2/3	2/3	2/3	1,4/2
80	-	-	-	-	2/3	2/3	1,4/2	1,4/2
100	-	-	-	-	-	2/3	1,4/2	1,4/2